


E2E UASB



E2E UASB

Technology

The E2E UASB (Upflow Anaerobic Sludge Blanket) Reactor is an advanced anaerobic treatment system for industrial and municipal wastewater.

It transforms organic waste into biogas using active granular anaerobic pellets. In the middle of the reactor is a dense bed of anaerobic sludge that breaks down organic material.

Wastewater inflow and external recirculation of clarified water ensures constant hydraulic upflow, and anaerobic digestion occurs. The bacteria decompose organic matter, converting it into biogas (mainly methane and carbon dioxide)

The Rectangular Settler Modules with built in Lamellas work as a high capacity 3-phase gas-water separator, and Biogas flotation device for liquid-solid separation, to retain the anaerobic granular sludge pellets.


The reactor is fully gas tight to prevent odor emissions, corrosion and minimizes sulfur deposits, ensuring long-term reliability and low-maintenance operation

Features

- Advanced UASB technology for industrial and municipal wastewater treatment,
- Rectangular, high capacity, 3-phase gas-water separator Settler Modules with built in Lamellas for best retention of granular sludge pellets
- External recirculation system ensuring constant hydraulic upflow under all conditions, for best mixing of anaerobic granular sludge pellets with waste water to secure best possible COD degradation and Biogas production.
- Efficient biogas collection and transport system from the reactor headspace to the gas treatment pipeline
- Simple rectangular or cylindrical flat-bottom tank design for cost-effective installation

Why to buy

- Cost effective Anaerobic Reactor for Waste Water Treatment in industrial and municipal applications, offering long-term reliability and high performance.
- UASB Installation in existing or new tank configuration, available in circular/rectangular tank design in steel or concrete
- Closed reactor design with optimized anaerobic granular sludge pellets retention, biogas recovery, reducing costs and improving sustainability
- Simple assembly and installation, best OPEX, low maintenance




Typical & Proven Process

- Anaerobic treatment of industrial wastewater, including paper production (DIP, Virgin), food, and beverage industries (brewery, dairy, sugar, etc.) and municipal applications
- Efficient operation with granular biomass (pellets) for optimized degradation and biogas generation
- Efficient sludge management and sludge growth

See the following Products as well

- E2E Anaerobic Reactor
- R2S Anaerobic Reactor
- Lime Trap
- Gas Flare
- Gas Buffer
- Desulfurization

Specifications



Technical Data

E2E-UASB Reactor Examples

Circular water height 7 m [H]

Diameter D [m]	Reactor volume [m ³]
4.5	110
9.5	500
16.5	1500
30	5000



Meri Environmental Solutions GmbH

Bodenseestr. 113
81243 Munich, Germany
Tel. +49 89 59 33 44
info@meri.de

Voith Meri Environmental Solutions, Inc.

2620 E. Glendale Avenue
P.O. Box 1262
Appleton WI 54911-1262, USA
Tel. +1 920 734-8485
info@meriusa.com

Meri Sistemas e Tecnologia Ltda.

R. Friedrich von Voith, 825
São Paulo – SP – 02995-000, Brasil
Tel. +55 11 3944-6644
meribrasil@meribrasil.com.br

**Meri Environmental Technology
(Kunshan) Co.,Ltd.**

No. 665 Jiande Road, Zhangpu Town,
Kunshan City, 215321 Jiangsu Province,
China
Tel. +86 51 28 68 90 834
info@meri.cn

www.meri.de



Note: All product-related data and information in this publication shall serve for information purposes only. They shall not be interpreted or intended to represent any kind of warranty or guarantee. The only legally binding statements are those contained solely within our quotations. Errors and omissions excepted. Technical data are subject to change.